



LANDON KINGSWAY

SAFETY, CONTROL & ENERGY MANAGEMENT

Fire Hydrant

Landon Kingsway stem stainless steel bodied, screw-down fire are hydrants manufactured to BS750.



High performance



Easy operation



Low weight



Working pressure
of PN16

Available in

Type 2 Screw down fire hydrant to BS750
80mm PN16 c/w Frost

Type 1 Screw down fire hydrant to BS750
Duckfoot pattern 80mm PN16

Heavy duty cast iron surface box to suit FH2
hydrant 230 x 380mm

Hydrant key & bar

80mm PN16 Duckfoot bend

Technical Specification

Manufactured to BS750

Kitemark QA

Stantons Secure bolt-down cap top

High performance

Low Weight 20kg

Low operating torque

Bubble Tight shut off

Outlet to BS 750 Part 5.2

Simple and easy operation

Spindle and Cap to BS5163

Working Pressure PN16

Max Temp +65°C

CC Clock Wise Closure

Outlet Flange to BS4504, BS EN1092-2
and ISO 7005-2 PN16

Materials

Body bonnet, top plate & gate BS 2789
Ductile Iron

Stem Stainless Steel

O-ring seals EPDM

Bolts Steel

Bush Acetal



1-3, Wharton Street Industrial Estate, Birmingham B7 5TR

sales@landonkingsway.com

+44 (0)121 327 7881



LANDON KINGSWAY

SAFETY, CONTROL & ENERGY MANAGEMENT

Related Products



Hose Reel

Manual or automatic wall mounted hose reel, available in 19mm and 25mm, fixed, swinging or recessed.



Foam Inlet Cabinet

Landon Kingsway's single-point foam inlet cabinet approved to BS 5306 Part 1.



Dry Riser Valve

Landon Kingsway's Dry Riser Valves, approved to BS 5041 Part 2, comes complete with red cap on chain, safety strap and padlock for security.



Inlet Breaching Valve

The Landon Kingsway inlet breaching valves have a universal pattern to BS 5041 Part 3, and come complete with non-return valve, rubber dust cap, 25mm drain valve, and cap/chain as standard.