







Severlek Emergency Buttons

The Severlek emergency button has a variety of uses where it is required to have a latching push button switch to sound an alarm or de-activate equipment.



 <p>Normally open contact</p>	 <p>Normally closed contact</p>	 <p>Sounds alarm</p>	 <p>De-activate equipment</p>
--	--	---	--

The switch has both a 'normally open' and a 'normally closed' contact pair which both change state on the switch being pressed.

Technical Specifications

Enclosure grey, epoxy coated die-cast aluminium with red plastic button.

Dimensions	89 x 71 x 95 mm
Fixing Centres	74 x 57 mm Ø8 mm
Protection Rating	IP65
Switch Rating	2KVA AC, 100W DC
Wire Size	2x 2.5 mm ²
Conduit Connection	PG16
Weight	0.4 kg

Available Models

- Manual Quick Release Mechanism
- Electromek MK II Manual Release 2x C/O Contacts
- Severlek Emergency Panic Button C/O Contacts
- Kingsway Emergency Panic Button
- Key Operated Isolation Switch

Related Products



Stand Alone Gas Detector

Landon Kingsway's Stand Alone Gas Detectors are available as single or multi channel, both come with sensors.



LKGSP4 Gas Safety Panel

The LKGSP4 is capable of detecting the presence of targeted gases; Natural gas, Carbon Monoxide or Liquid Petroleum.



Battery Backup Trickle Charger

Landon Kingsway's Battery Back-up Trickle Charger has ample battery space provided in all models and suitable for a wide range of applications.



GDP2 Gas Detection Panel

GDP2 can be used as a single or two zone gas detection and shut off system.