

DN80 Type 1 Fire Hydrant

DN80 Type 1 Fire Hydrant are WRAS approved for ground level connection of fire service equipment to the water main. Manufactured and kite marked to BS570, BS EN1074 part 2, EN 14339 and BSEN1074, the Type 1 fire hydrant is suitable for use with water and neutral liquids, to a maximum working pressure of 16 Bar.

Features

- Auto drain frost valve
- High Kv 113 (2401 ltr/min)
- Fully tested hydrostatically to 16bar
- WRAS approved for potable (drinking) water.
- Kitemark QA
- Secure bolt down cap top
- High performance
- Low Weight
- Low operating torque
- Bubble Tight shut off
- Simple and easy operation
- Spindle and Cap to BS5163
- Working Pressure PN16
- Working Temp -10°C to 70°C
- Insulation essential for temperatures of 0°C and below
- Clock Wise Closure
- Inlet Flange suitable for multiple flange connections
- BS4504, BS EN1092-2 and ISO 7005-2, PN10/16 and BS10 Table D/E
- Outlet 2½" London round thread outlet to BS 750



Construction Materials

- Body Body Bonnet, top plate & gate: BS 2789 Ductile Iron
- Stem Stainless Steel 316
- Elastomers: NBR
- Bolts Steel
- Bush Acetal
- Finish Wras Approved Epoxy Coated 250 microns to RAL5017

Part Number	Description	Cap Colour	PN10	PN16	BS10 Table D/E	Stopper
LK/14115	Hydrant Type FH1 (Type 1) for Main End	Black	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Allows water run back



If you have any questions or need any help then please contact our sales office.