

FUEL TANK ALARM PROBES

Single or double Fuel Tank Alarm Probes are used in conjunction with fuel tank alarms for indicating high level, low level or bund alert as required.

If both high and low-level alerts are requirements of the fuel storage tank level alarm, then a double probe should be purchased. If all three alerts are required, then a double and a single fuel tank level probe should be used.

They are installed by lowering the sensor to the desired set depth.

The standard code for the single fuel tank level switch is designed for use on steel tanks. Please see the accessories table for the kit required to adapt it for plastic tanks.

Features

- For use with mains or battery tank level alarms
- High, low or bund alerts
- 5m or 9m fuel tank probe cable
- 1 1/2" Female BSP brass cap
- 1 x Grommet
- Buna, nylon, stainless steel parts
- Temp Range: -20°C - +80°C
- For diesel, fuels, light oils and water

Single Probe



Double Probe



Part Number	Description	Lead Length
40901211	Single Fuel Tank Alarm Probe 6m	6m
40901212	Single Fuel Tank Alarm Probe 9m	9m
40901213	Double Fuel Tank Alarm Probe - For high and low level 6m	6m
40901214	Double Fuel Tank Alarm Probe - For high and low level 9m	9m



If you have any questions or need any help then please contact our sales office.