

LK16237 & LK16238 FOAM SPREADER



Part Number	Description	Type	Connection BSPP
LK16237	Foam Spreader	Straight	2 1/2"
LK16238	Foam Spreader	Straight	3"

The Landon Kingsway Foam Spreader is a critical discharge component used within fixed foam firefighting systems, designed to efficiently distribute firefighting foam throughout protected hazard areas. Installed at the termination point of the foam distribution pipework, the spreader converts the incoming foam solution into a controlled discharge pattern, ensuring rapid and effective coverage of enclosed spaces containing flammable liquids and high-risk equipment.

Typically utilised in transformer chambers, oil storage compounds, fuel pump rooms, generator enclosures, and boiler houses, the foam spreader enables firefighting personnel to introduce foam remotely via a dedicated foam inlet, minimising personnel exposure to hazardous environments during an emergency. The tapered internal design promotes uniform foam

distribution while helping to maintain the performance characteristics required for fixed foam suppression systems. Manufactured from heavy-duty steel and finished in a durable blackcoating, the foam spreader is designed to withstand harsh environmental conditions and provide long-term operational reliability. Available with either 2½" or 3" BSPP connections, the unit integrates seamlessly into fixed pipework installations and is suitable for use as part of systems designed in accordance with British standard recommendations. A maximum of three foam spreaders may be connected to a single foam inlet pipe, allowing effective protection of larger risk areas.

Key Features

- Designed for fixed foam firefighting installations.
- Provides effective and controlled foam distribution within protected compartments.
- Suitable for oil storage areas, transformer chambers, boiler rooms, generator enclosures, and other high-risk applications.
- Tapered outlet design for improved foam spread characteristics.
- Heavy-duty mild steel construction.
- Durable black powder-coated finish.
- Available with 2½" BSPP and 3" BSPP connections.
- Maximum working pressure: 14 bar (200 psi).
- Outlet cross-sectional area compliant with British Standard requirements.
- Suitable for use with Landon Kingsway foam inlet assemblies and associated firefighting equipment.

Typical System Operation

During a fire emergency, foam concentrate is introduced through a dedicated foam inlet cabinet / connection and transported via fixed pipework to the foam spreader. The spreader then disperses the foam evenly throughout the protected enclosure, creating a foam blanket over the hazard area to suppress vapours, cool surfaces, and assist in extinguishing flammable liquid fires.

This version reads more like a modern fire protection datasheet and better reflects the product's application in generator, transformer and fuel storage environments.

